

# SUBMITTAL DATA FOR PROPOSAL

## Flexmaster U.S.A.® CBD-BO3-HOK-2U

### SHEET METAL FITTINGS



The Flexmaster U.S.A.® CBD-BO3-HOK-2U is manufactured from heavier, galvanized steel to meet SMACNA and UMC Standards for commercial construction.

The CBD-BO3-HOK-2U should be installed using SMACNA installation standards.

#### Features

- Heavy Gauge G90 Galvanized Steel Fitting
- Damper blade equal to the fitting gauge
- BO3, Build-Out (2"), 3/8" square shaft, U-bolt, nylon bushings, locking quadrant, handle
- Factory Sealed Seams

#### Flexmaster U.S.A.® BO3

##### BO3

- 2" Build out
- Locking Quadrant
- 3/8" Aluminum Square Shaft
- Nylon Bushing



Order Size	Diameter	Cone Diameter	Hole Cut Diameter	Barrel Length	Cone Length	Body Gauge	Blade Gauge
4"	3 7/8"	5 7/8"	5 3/4"	7"	3"	24	24
5"	4 7/8"	6 7/8"	6 3/4"	7"	3"	24	24
6"	5 7/8"	7 7/8"	7 3/4"	7"	3"	24	24
7"	6 7/8"	8 7/8"	8 3/4"	8"	3"	22	22
8"	7 7/8"	9 7/8"	9 3/4"	9"	3"	22	22
9"	8 7/8"	10 7/8"	10 3/4"	11"	3"	20	20
10"	9 7/8"	11 7/8"	11 3/4"	12"	3"	20	20
12"	11 7/8"	13 7/8"	13 3/4"	13"	3"	20	20
14"	13 7/8"	15 7/8"	15 3/4"	15"	3"	20	20
15"	14 7/8"	16 7/8"	16 3/4"	16"	3"	20	20
16"	15 7/8"	17 7/8"	17 3/4"	17"	3"	20	20
18"	17 7/8"	19 7/8"	19 3/4"	19"	3"	20	20
20"	19 7/8"	21 7/8"	21 3/4"	21"	3"	20	20

(+/-) 1/8" Tolerance on all Sizes  
 Collar to comply per HOK specifications.  
 Length of collar for each fitting to match or exceed damper blade diameter.  
 Damper blade will be centered on collar.

Flexmaster U.S.A.®  
 5235 Ted Street  
 Houston, TX 77040 USA  
 Tel. +1.713.462.7694  
 Fax +1.713.939.8441  
 www.FlexmasterUSA.com  
 www.Masterduct.com

**FLEXMASTER U.S.A.®**  
 A MASTERDUCT COMPANY