

# SUBMITTAL DATA

## Flexmaster U.S.A.® Saddle Taps

### SHEET METAL FITTINGS

The Flexmaster U.S.A.® Saddle Tap fittings are manufactured from 26 gauge, or heavier, galvanized steel to meet SMACNA and UMC Standards for commercial construction.

The Saddle Tap fittings are sized for flex duct and can be made to fit up to 24" spiral pipe. The Saddle Tap fittings can be ordered as straight FL, straight FL 45° or our high efficiency STO in the 90°, 45° or Center model.

The Saddle Tap fittings should be installed using SMACNA installation standards.



STO ST 45°



STO ST 90°



STOC ST



FL ST



FL ST 45°

### Optional Features

#### Gauge Options: standard

26 ga

24 ga

22 ga

#### Damper Options:

BO3, Build-Out (2"), 3/8" square shaft, U-bolt, nylon bushings, locking quadrant, handle

BO4, Build-Out (2"), 3/8" square shaft, U-bolt, nylon bushings, Rossi Everlock locking quadrant, handle

#### Material Options:

Aluminum

Stainless steel



- BO3**
- 2" Build out
  - Locking Quadrant
  - 3/8" Aluminum Square Shaft
  - Nylon Bushing



- BO4**
- 2" Rossi (Everlock) Build out
  - Locking Quadrant
  - 3/8" Aluminum Square Shaft
  - Nylon Bushing